




TRAXON

Project: _____
Type: _____



ProPoint Kontour Round Wide RGBW

The Traxon ProPoint Kontour is an AC line powered exterior luminaire used to distinguish facades, walls, and architectural borders with a concentrated, even radiance. ProPoint Kontour's compact, lowprofile design is available in four lengths, two widths and is combined with a clip mounting system for efficient installation. This product is intended for use in high-quality colored light applications.



Product Specifications

	300mm	600mm	1200mm	2400mm
Model	Kontour Round Wide			
Light Source	RGBW (White CCT: 4000K)			
LED Quantity	RGBW / 4-in-1 LED cluster x 30pcs	RGBW / 4-in-1 LED cluster x 60pcs	RGBW / 4-in-1 LED cluster x 120pcs	RGBW / 4-in-1 LED cluster x 240pcs
Pixel Options	1PXL	1PXL or 2PXL	1PXL, 2PXL or 4PXL	1PXL, 2PXL, 4PXL or 8PXL
Beam Angle	100° x 125°			
Luminous Flux	173 lm	347 lm	648 lm	1383 lm
Efficacy	32 lm/W			
Lumen Maintenance	L70 @25°C 81,000hrs			
Cover Lens	Round diffused UV stable acrylic			
Housing	Extruded aluminum			
Housing Finish Options	Gray (RAL7015), Black (RAL9005), White (RAL9003)			
Mounting	Low Profile Mounting Brackets (x2 per length)			
Dimensions (L)	300mm / 11.8"	600mm / 23.6"	1200mm / 47.2"	2400mm / 94.5"
(W x H)	75mm x 89.4mm / 3" x 3.5"			
Weight	1.35 kg / 2.98 lbs.	1.86 kg / 4.10 lbs.	3.11 kg / 6.86 lbs.	5.42 kg / 11.95 lbs.
EPA (sq.ft)	Front	0.078		
	Side	0.392	0.630	1.173
	Front 45°	0.2771	0.4454	0.8293
				1.6600
Regulatory Listing & Safety Approval	CE, IEC 60598-2-3, 3G ANSI C136.31, IK07			
Operating Temperature	-30°C to +55°C / -22°F to +131°F			
Storage Temperature	-40°C to +80°C / -40°F to +176°F			
Environment	Outdoor (IP66), suitable for coastal environments			
Humidity	85%, non-condensing			

Electrical Specifications

Input Voltage	220-240V AC 50/60Hz			
Power Consumption	5W	10W	20W	40W
Power Factor	≥ 0.9			

System Specifications

Control	DMX 512
Power Supply	Integral
Addressing Options	Auto-Addressed with Data Injector
Pixel Control	Standard luminaire controlled by 300mm / 12". Factory configurable pixel control on request, check with your local sales office for more information.

LED CHARACTERISTICS Because LEDs are semiconductor devices, their performances are subject to inherent variability commonly found in semiconductor industry. To improve consistency in performance across the same product, LED manufacturers "sort" LEDs into bins according to different preset parameters, such as forward driving voltage, illumination, etc. Whereas binning is a sorting function, it is not a correction process. Inherent variability in the manufacturing process results always in different binning distributions according to different production lots. Traxon uses automatically binned LEDs on its products, thereby minimizing output variations within the model range.

As with all electronic devices, LED output degrades over time – a term called lumen depreciation. This also explains why it is nearly impossible to expect photometric performances of two LED products with different service life spans to be the same. The rate of LED degrade is a complicate function of many factors such as operating efficiency, duration of continuous operation, and more significantly, environmental conditions (ambient temperature for example). If allowed working under optimal operating temperature range and with good ventilation, LED devices enjoy long service lives over conventional light sources. When using/installing LED devices, care should be taken to ensure that the devices will operate within the operating conditions specified in respective product literature.

This product contains a light source of energy efficiency class G to Regulation (EU) No 2019/2015.
Lumen measurement complies with LM-79-05 standard.
Lumen maintenance is calculated based on LM-80 compliant measurement.



TRAXON


www.traxon-ecue.com

©2023 TRAXON TECHNOLOGIES. ALL RIGHTS RESERVED. TRAXON™, TX CONNECT®, ARE TRADEMARKS OF TRAXON TECHNOLOGIES. U.S. PATENTS, E.U. PATENTS, JAPAN PATENTS, OTHER PATENTS PENDING. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.



Photometrics

Optics	100° x 125°
--------	-------------



Color	Luminous Flux (lm)	Efficacy (lm/W)
300mm		
RGBW (full-on)	173.3	32.4
RGB	116.6	27.9
Red	27.2	15.4
Green	73.3	41.4
Blue	16.1	9.0
White	56.3	31.8
600mm		
RGBW (full-on)	346.9	32.5
RGB	233.5	28.1
Red	54.5	15.5
Green	146.8	42.1
Blue	32.1	9.1
White	112.7	33.9
1200mm		
RGBW (full-on)	648.2	30.4
RGB	426.7	25.6
Red	99.4	14.2
Green	274.8	39.1
Blue	57.6	8.2
White	220.0	31.3
2400mm		
RGBW (full-on)	1382.9	32.4
RGB	930.9	27.9
Red	216.1	15.6
Green	585.9	42.1
Blue	128.6	9.2
White	449.9	31.5

Center beam Lux/klm	Beam width (m)	
	V	H
1146	1.95m	1.25m
287	3.89m	2.51m
127	5.84m	3.76m
72	7.78m	5.01m
46	9.73m	6.26m
32	11.67m	7.52m


IES and LDT files are available for download from the Traxon website.





ProPoint Kontour Round Wide RGBW


Dimensions






ProPoint Kontour Round Wide RGBW

Mounting







ProPoint Kontour Round Wide RGBW

System Diagram

Wiring Information Details

ProPoint Kontour Wide -CE

220V-240V

Model	Power Consumption (Typ.)	Input Voltage	Max Connected Chain
300mm	5W	220-240V	512
600mm	10W	220-240V	320
1200mm	20W	220-240V	150
2400mm	40W	220-240V	80

Accessories (ETL / CE)

Model No.	Description	Item Code
PP.AC.100001	ProPoint Linear/Kontour Injector Box	AM374890055
PP.AC.100002	ProPoint Linear/Kontour Injector Box BL	AM374900055
PP.AC.100003	ProPoint Linear/Kontour Injector Box WT	AM374910055
PP.AC.600000	PP LIN/KON End Cap W / TERM.	AM380550055
PP.AC.400000	ProPoint RJ45 Field Install Connectors (pair)	AM380560055

Accessories (CE)

Cable Type	Model No.	Description	Item Code
Cable A*	PP. A2.303000	3M PP Linear Power Input Cable CE	AM374840055
Cable B*	KO.KB.610000	10M Kontour PWR/DATA INT CBL CE	AM357520155
Cable B*	KO.KB.601000	1M Kontour PWR/DATA INT CBL CE	AM357490155
Cable B*	KO.KB.602000	2M Kontour PWR/DATA INT CBL CE	AM357500155
Cable B*	KO.KB.603000	3M Kontour PWR/DATA INT CBL CE	AM357510155

* All cables come pre-wired with male / female connectors.



ProPoint Kontour Round Wide RGBW

Ordering

Model Number

KXX	.	3	.	9	4	4	6	2	.	X	.	XX
Kontour Length	Width	Control	Color	CCT	Approbation	Lens			Finish	Pixel Config		
K1L: 300mm	3: Wide	9: DMX	4: RGBW	4: 4000K	6: CE	2: Diffused Round Lens			1: Gray	01: 1PXL		
K2L: 600mm									2: Black	02: 2PXL		
K4L: 1200mm									3: White	04: 4PXL		
K8L: 2400mm										08: 8PXL		

*Abbreviations in Description

WD: Wide NW: Narrow R: Round BL: Black WT: White

Fixtures

Model No.	Description	Item Code
K1L.3.944621.01	ProPoint Kontour R 0.3 WD RGBW 1PXL CE	AM403710055
K2L.3.944621.01	ProPoint Kontour R 0.6 WD RGBW 1PXL CE	AM403730055
K2L.3.944621.02	ProPoint Kontour R 0.6 WD RGBW 2PXL CE	AM404550055
K4L.3.944621.01	ProPoint Kontour R 1.2 WD RGBW 1PXL CE	AM403750055
K4L.3.944621.04	ProPoint Kontour R 1.2 WD RGBW 4PXL CE	AM404570055
K8L.3.944621.01	ProPoint Kontour R 2.4 WD RGBW 1PXL CE	AM403770055
K8L.3.944621.08	ProPoint Kontour R 2.4 WD RGBW 8PXL CE	AM404590055
K1L.3.944622.01	ProPoint Kontour R 0.3 WD RGBW 1PXL BL CE	AM403790055
K2L.3.944622.01	ProPoint Kontour R 0.6 WD RGBW 1PXL BL CE	AM403810055
K2L.3.944622.02	ProPoint Kontour R 0.6 WD RGBW 2PXL BL CE	AM404610055
K4L.3.944622.01	ProPoint Kontour R 1.2 WD RGBW 1PXL BL CE	AM403830055
K4L.3.944622.04	ProPoint Kontour R 1.2 WD RGBW 4PXL BL CE	AM404630055
K8L.3.944622.01	ProPoint Kontour R 2.4 WD RGBW 1PXL BL CE	AM403850055
K8L.3.944622.08	ProPoint Kontour R 2.4 WD RGBW 8PXL BL CE	AM404650055
K1L.3.944623.01	ProPoint Kontour R 0.3 WD RGBW 1PXL WT CE	AM403870055
K2L.3.944623.01	ProPoint Kontour R 0.6 WD RGBW 1PXL WT CE	AM403890055
K2L.3.944623.02	ProPoint Kontour R 0.6 WD RGBW 2PXL WT CE	AM404670055
K4L.3.944623.01	ProPoint Kontour R 1.2 WD RGBW 1PXL WT CE	AM403910055
K4L.3.944623.04	ProPoint Kontour R 1.2 WD RGBW 4PXL WT CE	AM404690055
K8L.3.944623.01	ProPoint Kontour R 2.4 WD RGBW 1PXL WT CE	AM403930055
K8L.3.944623.08	ProPoint Kontour R 2.4 WD RGBW 8PXL WT CE	AM404710055



ProPoint Kontour Round Wide RGBW

[Ordering](#)

Accessories (ETL / CE)

Model No.	Description	Item Code
PP.AC.100001	ProPoint Linear/Kontour Injector Box	AM374890055
PP.AC.100002	ProPoint Linear/Kontour Injector Box BL	AM374900055
PP.AC.100003	ProPoint Linear/Kontour Injector Box WT	AM374910055
PP.AC.600000	PP LIN/KON End Cap W / TERM.	AM380550055
PP.AC.400000	ProPoint RJ45 Field Install Connectors (pair)	AM380560055

Accessories (CE)

Model No.	Description	Item Code
PP. A2.303000	3M PP Linear Power Input Cable CE	AM374840055
KO.KB.610000	10M Kontour PWR/DATA INT CBL CE	AM357520155
KO.KB.601000	1M Kontour PWR/DATA INT CBL CE	AM357490155
KO.KB.602000	2M Kontour PWR/DATA INT CBL CE	AM357500155
KO.KB.603000	3M Kontour PWR/DATA INT CBL CE	AM357510155

Accessories (Optional)

Model No.	Description	Item Code
KO.AA.900010	Kontour Safety Cable 0.25M (10")	AM403000055

